

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

NTS LABS, LLC DETROIT 12601 Southfield Road Detroit, MI 48223

Mr. Eric Loucks Phone: 313 659 2852 and 870 574 0031

MECHANICAL

Valid To: December 31, 2023 Certificate Number: 0214.08

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following mechanical tests:

Test Type 1:	Test Capabilities 1:	Test Method(s) ² :
Hydraulic Linear Actuation Rotary Actuation	Up to 35,000 pounds, Up to 12 in Up to 100,000 in/lbs +/- 45°	DET OPS 012 (Linear Actuation Rotary Actuation)
Burst	(0 to 20,000) psi	DET OPS 012
Proof Pressure	(0 to 20,000) psi	DET OPS 012
Impulse Cycling	(0 to 8,000) psi	SAE ARP 1383B (Impulse Cycling)
Flow	(0.1 to 300) 1pm	DET OPS 014 (Flow)
Dynamometer Driveline: Performance, Fatigue, Durability	Up to 600 HP, Torque Up to 6,000 ft/lbs, Speed Up to 14,000 RPM	GMW15788
Hybrid/Electric: Performance, Fatigue	Hot and Cold Fluid Flow	DET OPS 14 (Flow)
Hybrid/Electric: Durability and Efficiency	600V, 600A, 14,000 RPM	IEC 60349-2 (except noise measurements and limits)
Environmental Simulation Temperature (High and Low)	(-55 to 150) °C	GMW 3172, MIL-STD-202 (F, G) Method 106; MIL-STD-810 Method 501 and 502(C, D, E, F, G); RTCA/DO-160 (F & G) Section 5; SAE J1455 (All SAE Revisions)

(A2LA Cert. No. 0214.08) Revised 10/11/2022

Page 1 of 2

Test Type 1:	Test Capabilities 1:	Test Method(s) ² :
Environmental Simulation (cont'd)		
Temperature and Humidity	Temperature: (20 to 150) °C RH: (5 to 98) %RH Temperature at 95 °C: 95 %RH	GMW 3172 MIL-STD-202 (F, G) Method 102; MIL-STD-810 Method 507 (C, D, E, F, G); RTCA/DO-160 (F & G) Section 6; SAE J1455 (All SAE Revisions)
Altitude	Up to 50,000 feet	MIL-STD-810 Method 506 (C, D, E, F, G); RTCA/DO-160 (F & G) Section 4; SAE J1455 (All SAE Revisions)
Thermal Shock	(-55 to 150) °C	GMW 3172; MIL-STD-202 Method 107 (F, G); MIL-STD-810 Method 503 (C, D, E, F, G)
IP Protection/Dust	1 cubic meter	GMW 3172; IEC 60529
Handling Drop	1 meter drop	GMW3172
Resistance to Chemicals	Military, Aerospace, Commercially Available Fluids	CS11982
Gravel Bombardment		SAE J400; DIN/ISO EN 20567-1
IP Protection Water High Pressure Spray Immersion	Up to 3,500 psi @ 93 °C	IEC 60529; DIN 400 50; ISO 20653; SAE J1455; GMW 3172
Highly Accelerated Stress Test (HAST)	Temp 105 to 160 °C	JESD: 22-A110B-HAST; 22-A110C-HAST

On the following products or types of products:

Automotive, Aerospace, Medical, Military, and Electrical/Electronic/Mechanical Components & Assemblies

¹ Also using customer-specified methods directly related to the parameters and types of tests listed above.

² When the date, edition, version, etc. is not identified in the scope of accreditation, laboratories may use the version that immediately precedes the current version for a period of one year from the date of publication of the standard measurement method, per part C., Section 1 of A2LA *R101 - General Requirements- Accreditation of ISO-IEC 17025 Laboratories*.



Accredited Laboratory

A2LA has accredited

NTS LABS, LLC DETROIT

Detroit, MI

for technical competence in the field of

Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 1st day of March 2022.

Vice President, Accreditation Services

For the Accreditation Council

Certificate Number 0214.08

Valid to December 31, 2023

Revised October 11, 2022