

### SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

#### SHAMROCK LABORATORY 1475 East Industrial Drive Itasca, IL 60143 Chris DiLullo Phone: 630 735 3917 Fax: 630 595 6395

#### MECHANICAL

Valid To: January 31, 2025

Certificate Number: 2748.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following tests on metals and fasteners:

Test	Test Methods		
Mechanical Testing			
Hardness			
Rockwell (HRB, HRC)	ASTM A370, E18		
Micro hardness			
Кпоор (500НК)	ASTM E384		
Hydrogen Embrittlement	ASME B18.6.4 (superseded 2005) <sup>1</sup> , B18.6.3		
Surface Finish	ASME B46.1		
Drive Torque Test	ASME B18.6.4 (superseded 2005) <sup>1</sup> , B18.6.3		
Torsional Test	ASME B18.6.4 (superseded 2005) <sup>1</sup> , B18.6.3		
Metallographic Evaluation			
Case Depth	SAE J423, J933		
Environment Simulation			
Salt Spray	ASTM B117; Whirlpool T23		
Humidity	ASTM D2247, A380/A380M (Section 7.2.5.2);		
	Whirlpool T22		

Page 1 of 4

(A2LA Cert. No. 2748.01) 10/17/2022

5202 Presidents Court, Suite 220 | Frederick, MD 21703-8398 | Phone: 301 644 3248 | Fax: 240 454 9449 | www.A2LA.org

### I. Dimensional Testing<sup>3</sup>

Parameter/Equipment	Range	$\mathrm{CMC}^2$ (±)	Comments <sup>1</sup>
Radius	(0.005 to 0.50) in	0.005 in	Optical comparator/MIL-STD- 120 (canceled 1996)
Angle	Up to 360°	2°	Optical comparator/MIL-STD- 120 (canceled 1996)
Threads: Dia./Length Internal/External –	Up to 0.750 in	0.0006 in	Optical comparator/ASME B1.2, B1.3M (superseded in 1994), B1.3
	Up to 0.750 in	0.0003 in	Micrometer/ASME B1.2, B1.3M (superseded in 1994), B1.3
Pitch Diameter (External)	Up to 0.750 in	0.0002 in	System 22, tri roll/ASME B1.2, B1.3M (superseded in 1994), B1.3
Major Diameter	Up to 0.750 in	0.0006 in	Optical comparator/ASME B1.2, B1.3M (superseded in 1994), B1.3
	Up to 0.750 in	0.0003 in	Micrometer/ASME B1.2, B1.3M (superseded in 1994), B1.3
Minor Diameter	Up to 0.750 in	0.0006 in	Optical comparator/ASME B1.2, B1.3M (superseded in 1994), B1.3
Functional Thread	Up to 0.750 in	N/A	Go/No-Go thread gages/ASME B1.2, B1.3M (superseded in 1994), B1.3)

Page 2 of 4

Parameter/Equipment	Range	$CMC^{2}(\pm)$	Comments <sup>1</sup>
Length (1D)	(0.001 to 6) in	0.0003 in	Caliper/MIL-STD-120 (canceled 1996)
	(0.001 to 12) in	0.0009 in	Caliper/MIL-STD-120 (canceled 1996)
	(0.001 to 2) in	0.0006 in	Length gage/MIL-STD-120 (canceled 1996)
	(0.001 to 6) in	0.0006 in	Optical comparator/MIL- STD-120 (canceled 1996)
Concentricity	(0.001 to 0.200) in	0.0005 in	TIR/Concentricity gage/ ASME B18.2.1
Perpendicularity	(0.001 to 1) in	0.001 in	Vision system/ASME B18.2.1
Head Height	Up to 6 in	0.0006 in	Optical comparator/ASME B18.6.4, (superseded 2005) <sup>1</sup> B18.6.3
Wobble Test	12° Max	1.0°	Indicator and fixtures/ASME B18.6.4, (superseded 2005) <sup>1</sup> B18.6.3
Recess Penetration	Up to 0.200 in	0.0006 in	Indicator and fixtures/ASME B18.6.4, (superseded 2005) <sup>1</sup> B18.6.3

<sup>&</sup>lt;sup>1</sup> This laboratory's scope contains withdrawn or superseded methods. As a clarifier, this indicates that the applicable method itself has been withdrawn or is now considered "historical" and not that the laboratory's accreditation for the method has been withdrawn.

Page 3 of 4

- <sup>2</sup> Calibration and Measurement Capability Uncertainty (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine measurements of nearly ideal measurement standards or nearly ideal measuring equipment. CMC's represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of k = 2. The actual measurement uncertainty of a specific measurement performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific measurement.
- <sup>3</sup> This laboratory does not offer commercial dimensional testing services. These tests are not equivalent to that of a calibration.

Page 4 of 4

(A2LA Cert. No. 2748.01) 10/17/2022





# **Accredited Laboratory**

A2LA has accredited

# SHAMROCK LABORATORY

## Itasca, IL

for technical competence in the field of

# Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 17<sup>th</sup> day of October 2022.

Mr. Trace McInturff, Vice President, Accreditation Services For the Accreditation Council Certificate Number 2748.01 Valid to January 31, 2025